

CC NOZZLE

sales@ccnozzle.com

ccnozzle.com

Common Wide-angle Spray Nozzle

W
1/8"-1" NPT
or BSPT(male)



Nozzle Dimension

Nozzle type		
Nozzle Dimension	Hexagon l(mm)	Nozzle length (mm)
1/8	14.3	31
1/4	14.3	34



Common application

- Clarify board of spraying air
- Cooling conveyer belt
- Film development
- Fire proofing
- Water curtain



Dimension and weight

For the highest for each style:



W Common Wide-angle Spray Nozzle design features

W Common Wide-angle Spray Nozzle can produce secondary wide-angle sector spraying shape and uniform spraying drop. The round spray hole and large flow channel offer you least barrier.

It can also be applied in spraying of air or steam. The nozzles have precise diversion area, to well master the slanting angle and spraying angle.

It is made of firm stick with a outer inlet joint.

Performance data

Air and steam

Capacity Size	Rated Orifice Dia. (mm)	Air capacity (L/m)				Steam capacity (L/min)				The coverage of 150mm	
		0.7bar	1.5bar	3bar	3.5bar	0.7bar	1.5bar	3bar	3.5bar	0.7bar	1.5bar
0.50	0.61	4.5	6.4	10.5	11.6	0.16	0.23	0.37	0.41	51	127
0.75	0.71	6.2	9.1	14.7	16.7	0.23	0.33	0.53	0.66	64	140
1	0.84	9.6	13.7	22	25	0.34	0.49	0.80	0.90	76	152
1.5	1.04	15.3	22	36	40	0.54	0.78	1.3	1.5	89	165
2	1.17	19.3	28	45	51	0.68	1.0	1.6	1.8	102	190
2.5	1.32	27	37	60	71	0.95	1.3	2.1	2.5	102	190
3	1.45	31	47	77	85	1.1	1.7	2.7	3.0	127	203
4	1.65	40	57	85	108	1.4	2.0	3.1	3.9	127	228
5	1.85	54	76	124	139	1.9	2.7	4.5	5.0	152	267
7.5	2.31	79	117	189	210	2.9	4.2	6.8	7.6	152	267
10	2.64	110	159	255	290	3.9	5.7	9.2	10.4	178	279
15	3.28	181	260	420	475	6.5	9.3	15.0	17.1	178	305
20	3.76	225	325	520	590	8.0	11.6	18.8	21	216	368
30	4.57	320	465	760	850	11.6	16.8	27	30	216	394

A Series Common Nozzle